



UTILIZARI:
 -Apa; aer; abur;
 -Produce petroliere
 -Alte fluide compatibile
 cu materialele robinetului
 -Temp.max. de lucru: 180°C

17	Piulita	AISI304
16	Saiba	AISI304
15	Surub	AISI304
14	Opritor	AISI304
13	Protectie maner	Plastic
12	Piulita	AISI304
11	Saiba	AISI304
10	Maner	AISI304
9	Presetupa	AISI304
8	Garnitura etansare	PTFE
7	Garnitura pres.	PTFE
6	Tija	AISI304
5	Inel "O"	15%R-PTFE
4	Inel de etansare	15%R-PTFE
3	Sfera	ASTM A351 Gr CF8
2	Corp lateral	ASTM A216WCB
1	Corp	ASTM A216WCB
REP	DENUMIRE	Material

Filet NPT	d	L	H	W	B	D	S	Factor Cv	Moment Kgf-cm
1/4"	11.6	60	51	95	12	18	14.1	6.6	40
3/8"	12.7	60	51	95	12.52	18	17.6	7.9	40
1/2"	15	63	55	95	15.8	22	21.7	11.2	54
3/4"	20	70	58.5	110	20.93	28	27.2	21	74
1"	25	82	73	135	26.64	34	33.9	34	104
1-1/4"	32	96	78.5	135	35.05	44	42.6	57	135
1-1/2"	38	107	90.5	165	40.9	50	48.7	80	180
2"	50	124	99	165	52.5	61.5	61.1	148	250
2-1/2"	65	164.6	127	215	69	76	76.9	265	480
3"	80	182.7	136	215	82	90	89.8	415	750
4"	100	217.7	172	325	106	115	115.4	780	1100

Desenat: F.I.V.	ROBINET CU OBTURATOR SFERIC		Verificat: S.S
EUDIS VALVES	OTEL CARBON	Model din 3 piese	NUME FISIER: Fig.9.40
	DN 1/4" -4"	PN conf.diagramei	DATA: 17.02.2016
	EUDIS S.A		Fig.9.40