



CONSTRUCTIE:

- Flanse normale dupa DIN2501/1,PN25;PN40
- ↳Gabarit DIN3202/1 linia F1
- Teste hidraulice DIN3230
- ↳Rezistenta:1.5xPN
- Etansare:1.1xPN

CARACTERISTICI TEHNICE:

- Presiune nominala: 25;40 [bar]
- Diametru nominal: 15-200 [mm]
- Temperatura de lucru: -29°...450°C
- Etansare 13Cr/13Cr

PN	DN	L	d1	d2	nxd3	c	b	H	Masa/Kg
25/40	15	130	95	65	4X14	45	16	60	2.6
	20	150	105	75	4X14	58	18	70	4.2
	25	160	115	85	4X14	68	18	110	6
	32	180	140	100	4X18	78	18	126	10.4
	40	200	150	110	4X18	88	18	136	13.4
	50	230	165	125	4X18	102	20	150	15.7
	65	290	185	145	8X18	122	22	150	27.6
	80	310	200	160	8X18	138	24	171	35.8
	100	350	235	190	8X22	162	24	185	41
	125	400	270	220	8X26	188	26	190	60
150	480	300	250	8X26	218	28	200	90	
25	200	600	360	310	12X26	278	30	280	185
40	200	600	375	320	12X30	285	34	50280	198

Presiunea nominala	Temperatura °C							
	120	200	250	300	350	400	425	450
Presiunea de serviciu maxima (bar)								
25	25	22	20	17	16	13	12	10
40	40	35	32	28	24	21	19	17

6	Capac	GP240GH
5	Garnitura	Grafit
4	Arc	X20Cr13(W1.4021)
3	Ventil	GP240GH
2	Inel de etansare corp	X20Cr13(W1.4021)
1	Corp	GP240GH
REP	DENUMIRE	MATERIAL
Desenat: F.I.V.	ROBINET DE RETINERE CU VENTIL	
EUDIS VALVES	DIN OTEL	Verificat: S.S
	DN 15-200	Nume Fisier: Fig.4.55 RO
	PN 25/40	DATA: 11.12.2014
EUDIS S.A.		Fig.4.55

We reserve the right to make such alterations in design, dimension, specifications and manufacture as are deemed necessary to ensure continued improvement