



UTILIZARI:
 -Apa; aer; abur;
 -Produce petroliere
 -Alte fluide compatibile
 cu materialele robinetului
 -Temp.max. de lucru: 180°C

17	Piulita	AISI304
16	Saiba	AISI304
15	Surub	AISI304
14	Opritor	AISI304
13	Protectie maner	Plastic
12	Piulita	AISI304
11	Saiba	AISI304
10	Maner	AISI304
9	Presetupa	AISI304
8	Garnitura etansare	PTFE
7	Garnitura pres.	PTFE
6	Tija	AISI316
5	Inel "O"	15%-R-PTFE
4	Inel de etansare	15%-R-PTFE
3	Sfera	ASTM A351 Gr CF8M
2	Corp lateral	ASTM A351 Gr CF8M
1	Corp	ASTM A351 Gr CF8M
REP	DENUMIRE	Material - Var.CF8M

Filet NPT	d	L	H	W	B	D	S	Factor Cv	Moment Kgf-cm
1/4"	11.6	59	51	95	12	18	14.1	6.6	40
3/8"	12.7	59	51	95	12.52	18	17.6	7.9	40
1/2"	15	63.3	55	95	15.8	22	21.7	11.2	54
3/4"	20	70.6	58.5	110	20.93	28	27.2	21	74
1"	25	82	73	135	26.64	34	33.9	34	104
1-1/4"	32	97	78.5	135	35.05	44	42.6	57	135
1-1/2"	38	109	90.5	165	40.9	50	48.7	80	180
2"	50	124.6	99	165	52.5	61.5	61.1	148	250
2-1/2"	65	162	127	215	69	76	76.9	265	480
3"	80	175	136	215	82	90	89.8	415	750
4"	100	216	172	325	106	115	115.4	780	1100

Desenat: F.I.V.

ROBINET CU OBTURATOR SFERIC

OTEL / INOX **Model din 3 piese** Verificat: S.S

DN 1/4" -4" **PN conf.diagramei** NUME FISIER: Fig.9.40 IN

EUDIS VALVES

EUDIS S.A. DATA: 05.08.2019

Fig.9.40 IN