



UTILIZARE:

- Apa ; aer; abur; produse petoliere
- Alte fluide compatibile cu materialele robinetului
- Temperatura maxima de lucru :180°C

DN	ØB	L	H	W	ØJ	ØG	ØN
8	11.1	90	61	105	11.1	13	17.2
10	11.1	90	61	105	11.1	13	17.2
15	15.8	90	61	105	15.8	17	21.3
20	20.5	94	70	125.5	20.5	22	26.9
25	25.4	108	74	175.5	25.4	28	33.7
32	31.8	116	82	198.2	33.8	37	42.4
40	38.1	132	89	248.5	39.8	43	11.1
50	50	144	97	248.5	50.8	54	11.1

17	Inel etansare	PTFE	
16	Piesa fixare scaun	Otel Inox AISI 316	
15	Holender	Otel Inox AISI 316	
14	Protectie plastic	PVC	
13	Surub opritor	Otel Inox 304	
12	Tija maner	Otel Inox 304	
11	Maner	Otel Inox 304	
10	Opritor	Otel Inox 304	
9	Presetupa	Otel Inox 304	
8	Inel etansare tija	PTFE	
7	Garnitura	PTFE	
6	Garnitura corp	PTFE	
5	Tija	Otel Inox AISI 316	
4	Sfera	Otel Inox AISI 316	
3	Scaun	PTFE	
2	Corp lateral	Otel Inox AISI 316	
1	Corp	Otel Inox AISI 316	
Nr.	DENUMIRE	MATERIAL	
Desenat: F.I.V.	ROBINET CU SFERA CU HOLENDERE		Verificat: S.S.
EUDIS VALVES	OTEL INOX	CAPETE PENTRU SUDURA	Nume fisier: Fig.9.69.IN.HOL.BW
	DN 15-50	PN 200	Data: 26.10.2020
	EUDIS S.A.		Fig.9.69.IN.HOL.BW